

EFE400 – Series

400W, 530W



Industrial



Automation



Test



Broadcast



Comms



Renewable



1 Output + standby

High power density: 400W on 6 x 3 inch footprint
Input fuse: Dual fuses (live and NEWtral)
Peak power: 530W for up to 10 sec.



Air Flow



Fan

Output power:	400W continuous, 530W peak power
Input voltage:	90 – 264Vac, 45 – 63Hz (440Hz with reduced PFC), 120 – 350Vdc
Output voltage:	12 or 24Vdc (non standard voltages available)
Efficiency:	Up to 90%
Warranty:	5 years

More information: www.emea.tdk-lambda.com/efe

EFE400M – Series

400W, 530W



Medical



Industrial



Automation



Test



Broadcast



Comms



Renewable



1 Output

High power density: 400W on 6.5 x 3.5 inch footprint
Isolation: 4kVac input to output (2 x MOPPs for IEC60601-1)
1.5kVac output to ground, 1.5kVac input to ground



Air Flow



Fan

Output power:	400W continuous, 530W peak power
Input voltage:	90 – 264Vac, 45 – 63Hz (440Hz with reduced PFC), 120 – 350Vdc
Output voltage:	12, 24 or 48Vdc (non standard voltages available)
Efficiency:	Up to 90% (87% if Standby Supply is fully loaded)
Warranty:	5 years

More information: www.emea.tdk-lambda.com/efe-m