

Modular Contact Block, momentary MTO

General Data

Type reference	MTO
Description	Modular Contact Block (positive opening contact)
Approvals	CCC, CSA, ENEC05, KEMA, CE, TÜV_Süd, UL, Zwangsöffnung
Nature of contact	1NC
Protection class	II (protective insulation)
Operation travel	6 mm
Connection type	screw connection 2x2.5mm ²
Contact material	AgNi
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 85°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million operations at rated load
Contact resistance NC	< 20 mOhm
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15 A600	DC13 Q600
Rated insulation voltage U _i	600 V	600 V
Rated operating voltage U _e	240V / 440V	440V / 250V / 125V / 60V / 24V
Rated operating current I _e	3A / 1.6A	0.12A / 0.2A / 0.4A / 1A / 2A
Breaking capacity	10I _e	1,1I _e
Continuous thermal current	16 A	

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)

Rated voltage U _e	250 V~ / 440 V~
------------------------------	-----------------

Rated current I_e 16(10) A / 10(6) A

Data acc. to UL508

Flammability class acc. to UL94 V0

General Data

Tightening torque (screw terminal) 0.8...1.0 Nm


Electrical Data acc. to UL 508

Ratings A600, 600 V AC

Fotografia:



Puntos de activación:



Esquema eléctrico:

