

Emergency-Stop - 2NC YVOO

General Data

Type reference	YV(O)(OO)(H)(OOI)(LOO)(LO)(_AU)(_R0)(_674)
Description	Emergency-stop Head, foolproof
Approvals	CE, TÜV_Süd, UR
Nature of contact	2NC / 2NC+1NO / 1NC
Degree of protection	IP65 / IP67 / IP69K
Connection type	Faston terminals 2.8 mm x 0.5 mm / soldering lug
Contact material	AgNi / AgNi, gold-plated 5µm
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	30,000
Electrical life (rated load)	30,000 at rated load
Contact resistance NO	< 20 mOhm/< 50 mOhm (Au)
Contact resistance NC	< 20 mOhm/< 50 mOhm (Au)
Bouncing time NO	< 10 ms
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage Ui	250 V	250V
Rated operating voltage Ue	35 V	35 V
Rated operating current Ie	5A	2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	5A	

Technical Data - Lamp

Lamp socket	none, with integrated LED
Max. lamp voltage	30 V AC/DC
Max. lamp output	8mA/4.5mA (bei 24 V DC/AC)
Definition	X1...anode, X2...cathode

Additional Data

Mounting aperture	16.2 mm
Tightening torque (mounting nut)	0.8 ... 1.5 Nm
Release	twist release, left or right
Mounting position	any
Standards	EN 60947-5-1, EN 60947-5-5, EN ISO 13850
Material group	I
Overvoltage category	II
Pollution degree	2

Electrical Features - 5µm gold-plating, type addition ...AU

Operational voltage	20 mV...35 V AC/DC
Operational current AC/DC	max. 100 mA
Ld	20% (NC)
B10d	250,000

Note

- with switching position indicator

- H= version with solder lug for hand soldering (YVOH..., YVOOH...)r

- _674 ...with aluminium nut for plate thickness: 1.5...3.0 mm

torque - mounting nut: 1.2 Nm

- _R0 ...0 ohm series resistor, with protective diode (series-connected)

LED cut-off voltage: max. 75 V (incl. protective diode)

If LED, max: 25 mA

Uf LED, typical: 3.2 V (20mA)

- Use partially insulated Faston clamps (for versions with Faston terminals)

Recommend Schlegel type "FHTI2,8x0,5_01"

0.5-1.5mm² (AWG 20-16)

-30°C - 75°C

Supplementary data for versions without 3rd contact assignment/illumination (type YVOO):

acc. to IEC/EN 60947-5-1 (VDE 0660 sect. 200)

AC15 B300: Ue/Ie 240V 1.5A

DC13 Q300: Ue/Ie 250V 0.27A

Note - applies to version "H"/solder lug:

When soldering the strands to the solder lugs, make sure that in the soldering process the necessary air and creepage distances between solder lug and mounting nut are not reduced (possibly caused by solder splashes or protruding strands).

Note - applies to version "_R0" (0 ohm series resistor):

The LED must not be operated without series resistor.

Do not connect terminals X1-X2 directly to voltage. Observe LED data!


Data acc. to UL508, IEC60947-5-5

Tightening torque (mounting nut) 0.8 ... 1.5 Nm (plastic nut)
1,2 Nm (metal nut)


Fotografia:



Dimensiones:



Esquema eléctrico:



Taladro de montaje:

