

GEN 2U – Series

3300 – 5000W



Industrial



Automation



Test



Interface: RS232/RS485, analogue (standard)
LAN, IEEE (optional)

Dynamic response: Fast speed option for Automotive

Output current: Up to 600A



Fan

Output power:	3300, 5000W
Input voltage:	Single-phase 170 – 265Vac, 47 – 63Hz (3300W only) Three-phase 170 – 265Vac or 342 – 460Vac
Output voltage:	8, 10, 15, 16, 20, 30, 40, 60, 80, 100, 150, 200, 300, 400, 500 or 600Vdc
Efficiency:	Up to 88%
Warranty:	5 years

More information: www.emea.tdk-lambda.com/gen2u

GEN 3U – Series

10000 – 15000W



Industrial



Automation



Test



Interface: RS232/RS485, analogue (standard)
LAN, IEEE (optional)

Output current: Up to 1000A



Fan

Output power:	10000, 15000W
Input voltage:	Three-phase 208Vac, 400Vac or 480Vac
Output voltage:	7.5, 10, 12.5, 20, 25, 30, 40, 50, 60, 80, 100, 125, 150, 200, 300, 400, 500, 600, 800, 1000, 1250 or 1500Vdc
Efficiency:	Up to 88%
Warranty:	5 years

More information: www.uk.tdk-lambda.com/gen3u