

HFE-1600 – Series

1600W



Redundancy: Internal ORing MOSFET & Current Share

High efficiency: Meet 80+ Standard gold

Interface: PMBus option



Output power:	1600W single unit, up to 8 kW in 19" 1U shelf
Input voltage:	85 – 265Vac, 47 – 63Hz
Output voltage:	12, 24, 32 or 48Vdc
Efficiency:	Up to 92%
Warranty:	3 years

More information: www.emea.tdk-lambda.com/hfe

HFE-1600-S1U/-D1U – Series

6000 – 8000W



HFE-1600-S1U: Parallel operation up to 5 units HFE-1600 (8000W total)

HFE-1600-D1U: 2 separate outputs for 2x 2 units HFE-1600 (2x 3000W)

High efficiency: Meet 80+ Standard gold

Interface: PMBus option and LAN option



Output power:	Up to 8kW in 19" 1U shelf
Input voltage:	85 – 265Vac, 47 – 63Hz
Output voltage:	12, 24, 32 or 48Vdc
Efficiency:	Up to 92%
Warranty:	3 years

More information: www.emea.tdk-lambda.com/hfe

HFE-2500 – Series

2500W



Redundancy: Internal ORing MOSFET & Current Share
High efficiency: Meet 80+ Standard platinum/gold
Interface: PMBus option



Output power:	2500W single unit, up to 10kW in 19" 1U shelf
Input voltage:	85 – 265Vac, 47 – 63Hz
Output voltage:	12, 24, 32 or 48Vdc
Efficiency:	Up to 92.5%
Warranty:	3 years

More information: www.emea.tdk-lambda.com/hfe

HFE-2500-S1U – Series

10000W



1U 19" shelf: Suitable for up to 4 rectifiers HFE-2500
High efficiency: Meet 80+ Standard platinum/gold
Interface: PMBus option and LAN option



Output power:	Up to 10kW in 19" 1U shelf
Input voltage:	85 – 265Vac, 47 – 63Hz
Output voltage:	12, 24, 32 or 48Vdc
Efficiency:	Up to 92.5%
Warranty:	3 years

More information: www.emea.tdk-lambda.com/hfe