



Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 520 x 270 x 110 mm

42660001	320 W / 140 W	230 V - 50/60 Hz	+20°C - +50°C	24 / 54	13	Click here for full technical specifications KG 4266
42661001	320 W / 140 W	120 V - 60 Hz	+20°C - +50°C	24 / 54	13	

Dimensions (H x W x D): 340 x 520 x 110 mm

42670001	400 W / 195 W	230 V - 50/60 Hz	+20°C - +50°C	24 / 54	14.8	Click here for full technical specifications KG 4267
42671001	400 W / 195 W	120 V - 60 Hz	+20°C - +50°C	24 / 54	14.8	

Dimensions (H x W x D): 520 x 320 x 110 mm

42680001	400 W / 155 W	230 V - 50/60 Hz	+20°C - +50°C	24 / 54	14.8	Click here for full technical specifications KG 4268
42681001	400 W / 155 W	120 V - 60 Hz	+20°C - +50°C	24 / 54	14.8	

Dimensions (H x W x D): 600 x 320 x 110 mm

42690001	500 W / 160 W	230 V - 50/60 Hz	+20°C - +50°C	24 / 54	15.8	Click here for full technical specifications KG 4269
42691001	500 W / 160 W	120 V - 60 Hz	+20°C - +50°C	24 / 54	15.8	