

Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 810 x 395 x 145 mm

42700001	600 W / 300 W	230 V - 50/60 Hz	+20°C - +50°C	24 / 54	30	Click here for full technical specifications KG 4270
42701001	600 W / 300 W	120 V - 60 Hz	+20°C - +50°C	24 / 54	30	
42702001	600 W / 300 W	400/460 V - 50/60 Hz 2~	+20°C - +50°C	24 / 54	33	

Dimensions (H x W x D): 980 x 395 x 145 mm

42710001	820 W / 480 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	33	Click here for full technical specifications KG 4271
42711001	820 W / 480 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	34	
42712001	820 W / 480 W	380/415 V - 50 Hz 3~ 400/460 V - 60 Hz 3~	+20°C - +55°C	24 / 54	38	

Dimensions (H x W x D): 1250 x 395 x 145 mm

42720001	1.1 kW / 710 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	44	Click here for full technical specifications KG 4272
42721001	1.1 kW / 710 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	44	
42722001	1.1 kW / 710 W	380/415 V - 50 Hz 3~ 400/460 V - 60 Hz 3~	+20°C - +55°C	24 / 54	45	

Dimensions (H x W x D): 1550 x 395 x 145 mm

42740001	1.5 k / 1.2 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	50	Click here for full technical specifications KG 4274
42741001	1.5 k / 1.2 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	50	
42742001	1.5 k / 1.2 kW	380/415 V - 50 Hz 3~ 400/460 V - 60 Hz 3~	+20°C - +55°C	24 / 54	55	