

SoliTherm ComPact

Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 500 x 280 x 200 mm

43040001	320 W / 200 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	18	Click here for full technical specifications KG 4304
----------	---------------	------------------	---------------	---------	----	--

Dimensions (H x W x D): 500 x 280 x 270 mm

43041001	320 W / 240 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	26
43042001	320 W / 240 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	26

Dimensions (H x W x D): 650 x 315 x 260 mm

43050001	550 W / 410 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	27.7	Click here for full technical specifications KG 4305
43051001	550 W / 410 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	33.7	
43052001	550 W / 410 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	33.7	
43080001	750 W / 470 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	27.7	Click here for full technical specifications KG 4308
43081001	750 W / 480 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	33.7	
43082001	750 W / 480 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	33.7	
43090001	850 W / 610 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	30	Click here for full technical specifications KG 4309
43091001	850 W / 600 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	36	
43092001	850 W / 600 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	36	
43100001	1 kW / 660 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	30	Click here for full technical specifications KG 4310
43101001	1 kW / 660 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	36	
43102001	1 kW / 720 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	36	

Note: The IP rating on the ambient side can be increased by using filter mats



SoliTherm ComPact recessed

Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
Dimensions (H x W x D): 715 x 372 x 260 mm (incl. 90 mm recess)						
43050081	550 W / 410 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	27.7	Click here for full technical specifications KG 4305
43051081	550 W / 410 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	33.7	
43052081	550 W / 410 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	33.7	
43080081	750 W / 470 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	27.7	Click here for full technical specifications KG 4308
43081081	750 W / 480 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	33.7	
43082081	750 W / 480 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	33.7	
43090081	850 W / 610 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	30	Click here for full technical specifications KG 4309
43091081	850 W / 600 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	36	
43092081	850 W / 600 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	36	
43100081	1 kW / 660 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	30	Click here for full technical specifications KG 4310
43101081	1 kW / 660 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	36	
43102081	1 kW / 720 W	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	36	

Note: The IP rating on the ambient side can be increased by using filter mats

