



SoliTherm ComPact

Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 980 x 395 x 260 mm

43150001	1.50 kW / 1.22 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	39.7	Click here for full technical specifications KG 4315
43151001	1.50 kW / 1.22 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	47.7	
43152001	1.50 kW / 1.22 kW	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	47.7	
43200001	2 kW / 1.6 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	44.2	Click here for full technical specifications KG 4320
43201001	2 kW / 1.6 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	50	
43202001	2 kW / 1.63 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	44.2	

Dimensions (H x W x D): 1,230 x 500 x 340 mm

43250001	2.5 kW / 1.97 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	67.5	Click here for full technical specifications KG 4325
43251001	2.5 kW / 1.97 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	73	
43252001	2.5 kW / 1.97 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	73	
43300001	3 kW / 2.38 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	67.5	Click here for full technical specifications KG 4330
43301001	3 kW / 2.42 kW	120 V - 50/60 Hz	+20°C - +55°C	24 / 54	75	
43302001	3 kW / 2.39 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	72.5	
43400001	4 kW / 3.18 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	69	Click here for full technical specifications KG 4340
43402001	4 kW / 3.17 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	72.5	

Note: The IP rating on the ambient side can be increased by using filter mats





SoliTherm ComPact recessed

Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 1045 x 452 x 270 mm (incl. 90 mm recess)

43150081	1.5 kW / 1.22 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	39.7	Click here for full technical specifications KG 4315
43151081	1.5 kW / 1.22 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	47.7	
43152081	1.5 kW / 1.22 kW	400/460 V - 50/60 Hz 2~	+20°C - +55°C	24 / 54	47.7	
43200081	2 kW / 1.6 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	44.2	Click here for full technical specifications KG 4320
43201081	2 kW / 1.6 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	50	
43202081	2 kW / 1.63 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	44.2	

Dimensions (H x W x D): 1,295 x 557 x 340 mm (incl. 90 mm recess)

43250081	2.5 kW / 1.97 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	67.5	Click here for full technical specifications KG 4325
43251081	2.5 kW / 1.97 kW	120 V - 60 Hz	+20°C - +55°C	24 / 54	73	
43252081	2.5 kW / 1.97 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	73	
43300081	3 kW / 2.38 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	67.5	Click here for full technical specifications KG 4330
43301081	3 kW / 2.42 kW	120 V - 50/60 Hz	+20°C - +55°C	24 / 54	75	
43302081	3 kW / 2.39 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	72.5	
43400081	4 kW / 3.18 kW	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	69	Click here for full technical specifications KG 4340
43402081	4 kW / 3.17 kW	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	72.5	

Note: The IP rating on the ambient side can be increased by using filter mats

