



Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 830 x 304 x 270 mm

570500001	550 W / 410 W	230 V - 50/60 Hz	-20°C - +55°C	IP 56	30	Click here for full technical specifications OC 5705
570510001	550 W / 410 W	120 V - 60 Hz	-20°C - +55°C	IP 56	35	
570520001	550 W / 410 W	400/460 V - 50/60 Hz 2~	-20°C - +55°C	IP 56	35	
570800001	750 W / 470 W	230 V - 50/60 Hz	-20°C - +55°C	IP 56	30	Click here for full technical specifications OC 5708
570810001	750 W / 480 W	120 V - 60 Hz	-20°C - +55°C	IP 56	35	
570820001	750 W / 480 W	400/460 V - 50/60 Hz 2~	-20°C - +55°C	IP 56	35	
570900001	850 W / 610 W	230 V - 50/60 Hz	-20°C - +55°C	IP 56	32	Click here for full technical specifications OC 5709
570910001	850 W / 600 W	120 V - 60 Hz	-20°C - +55°C	IP 56	37	
570920001	850 W / 600 W	400/460 V - 50/60 Hz 2~	-20°C - +55°C	IP 56	37	

Dimensions (H x W x D): 900 x 304 x 270 mm

571000001	1 kW / 660 W	230 V - 50/60 Hz	-20°C - +55°C	IP 56	38	Click here for full technical specifications OC 5710
571010001	1 kW / 660 W	120 V - 60 Hz	-20°C - +55°C	IP 56	45	
571020001	1 kW / 720 W	400/460 V - 50/60 Hz 2~	-20°C - +55°C	IP 56	45	

