



Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 1150 x 395 x 270 mm

571500001	1.5 kW / 1.22 kW	230 V - 50/60 Hz	-20°C - +55°C	IP 56	48	Click here for full technical specifications OC 5715
571510001	1.5 kW / 1.22 kW	120 V - 60 Hz	-20°C - +55°C	IP 56	55	
571520001	1.5 kW / 1.22 kW	400/460 V - 50/60 Hz 2~	-20°C - +55°C	IP 56	55	
572000001	2 kW / 1.6 kW	230 V - 50/60 Hz	-20°C - +55°C	IP 56	49	Click here for full technical specifications OC 5720
572010001	2 kW / 1.6 kW	120 V - 60 Hz	-20°C - +55°C	IP 56	53	
572020001	2 kW / 1.63 kW	400/460 V - 50/60 Hz 3~	-20°C - +55°C	IP 56	50	

Dimensions (H x W x D): 1550 x 495 x 355 mm

572600001	2.5 kW / 1.97 kW	230 V - 50/60 Hz	-20°C - +55°C	IP 56	68	Click here for full technical specifications OC 5721
572610001	2.5 kW / 2 kW	120 V - 60 Hz	-20°C - +55°C	IP 56	75	
572620001	2.5 kW / 2 kW	400/460 V - 50/60 Hz 2~	-20°C - +55°C	IP 56	75	
573000001	3 kW / 2.4 kW	230 V - 50/60 Hz	-20°C - +55°C	IP 56	70	Click here for full technical specifications OC 5731
573110001	3 kW / 2.4 kW	120 V - 60 Hz	-20°C - +55°C	IP 56	78	
573120001	3 kW / 2.4 kW	400/460 V - 50/60 Hz 3~	-20°C - +55°C	IP 56	75	
574100001	4 kW / 3.3 kW	230 V - 50/60 Hz	-20°C - +55°C	IP 56	72	Click here for full technical specifications OC 5741
574120001	4 kW / 3.3 kW	400/460 V - 50/60 Hz 3~	-20°C - +55°C	IP 56	72	

