## RFE2500 - Series

#### 2500W









High efficiency: Meet 80+ Standard platinum/gold

Redundancy: n+1 operation with integrated ORing FET

Paralleling: With active current share Signalling: Full array of signals

2500W Output power:

85 - 265Vac, 47 - 63Hz Input voltage: 12, 24, 32 or 48Vdc Output voltage:

Efficiency: Up to 92% Warranty: 3 years

More information:









www.emea.tdk-lambda.com/rfe

### RFE1600 - Series

#### 1600W











Redundancy: n+1 operation with integrated ORing FET

Size: Flat shape for 1U integration Input: Wide range 85 - 265Vac





Output power: 1600W

Input voltage: 85 - 265Vac, 47 - 63Hz Output voltage: 12, 24 or 48Vdc

Efficiency: Up to 92% Warranty: 3 years

More information: www.emea.tdk-lambda.com/rfe

# RFE1000 - Series

#### 1000W







High efficiency: **Up to 89%** 

Redundancy: n+1 operation with integrated ORing diode

Size: Flat shape for 1U integration

Input: Wide range 85 – 265Vac without derating



1000W Output power:

85 - 264Vac, 47 - 63Hz Input voltage:

Output voltage: 24, 32 or 48Vdc Efficiency: Up to 89%

Warranty: 2 years

More information: www.emea.tdk-lambda.com/rfe