

reddot design award
winner 2010

RFID reader with USB interface RRJ_RFID_USB

Description:

- - panel cut-out Ø 22.3 mm
- - 13,56 MHz
- - supports the Standards ISO 14443A/B (MIFARE-Classic/-DESFire), ISO 15693 and compatibles like EM4135, EM4043
- - read and write function
- - USB drivers for Windows, Linux, Android 4.2 and Macintosh OSX
- - 2 operating modes: cyclic transmission with individual transmission (continuous operation) or manual transmission (on/off)
- - LED status illumination
- - supply voltage of 5V/DC is necessary
- - cable length: 80 cm (other lengths on request)

Category:

RFID

Series:

RONTRON-R-JUWEL

Panel cut-out:

Ø 22.3 mm

Degree of protection:

IP65 / IP69k

Colour

silver-coloured

Shape:

round

Necessary accessory



ESRT1_B



ESRT1_G



ESRT1_R



ESRT1_S



ESRT1_Y



ESRT2_B



ESRT2_G



ESRT2_R



ESRT2_S



ESRT2_Y



ESRT4_B



ESRT4_G



ESRT4_R



ESRT4_S



ESRT4_Y



ESRT8_B



ESRT8_G




ESRT8_R



ESRT8_S



ESRT8_Y



Optional accessory



LR22K5DUO_GB_619



RRJ_RFID_HR_LBG

RRJ_RFID_HR_SW



RRJ_RFID_HR_WS

