



Part-no.	Cooling capacity L35L35	Voltage / Frequency	Operating temp. range	Ingress IP protection	Weight (Kg)	QR Code
Dimensions (H x W x D): 206 x 154 x 135 mm						
3050303	50 W	24 V DC	-20°C - +65°C	IP 66	3.3	Click here for full technical specifications TG 3050
Dimensions (H x W x D): 302 x 158 x 137 mm						
3050305	50 W	24 V DC	-20°C - +65°C	IP 66	3.9	
Dimensions (H x W x D): 304 x 200 x 138 mm						
3102303	100 W	24 V DC	-20°C - +65°C	IP 66	5.9	Click here for full technical specifications TG 3102
Dimensions (H x W x D): 306 x 302 x 140 mm						
3102305	100 W	24 V DC	-20°C - +65°C	IP 66	7.4	
Dimensions (H x W x D): 400 x 180 x 171 mm						
3152303	150 W	24 V DC	-20°C - +65°C	IP 66	9	Click here for full technical specifications TG 3152
3152308	175 W	48 V DC	-20°C - +65°C	IP 66	9	
3200303	200 W	24 V DC	-20°C - +65°C	IP 66	9	Click here for full technical specifications TG 3200
3200308	250 W	48 V DC	-20°C - +65°C	IP 66	9	
Dimensions (H x W x D): 500 x 188 x 174 mm						
3152305	150 W	24 V DC	-20°C - +65°C	IP 66	12.7	Click here for full technical specifications TG 3152
3152310	175 W	48 V DC	-20°C - +65°C	IP 66	12.7	
3200305	200 W	24 V DC	-20°C - +65°C	IP 66	12.7	Click here for full technical specifications TG 3200
3200310	250 W	48 V DC	-20°C - +65°C	IP 66	12.7	