

Air / Water Heat Exchanger RK 2125 A-230V



Product Features

Brand Name:	SoliTherm
Order Number:	2125010
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
IP class EN 60529:	IP 54
Optional:	With solenoid valve article no. 2125000
Approvals:	CE, RoHS
Taric Code:	84158300

Technical data RK 2125 A-230V

Cooling capacity L35W10 (200 l/h):	2,5 kW
Cooling capacity L35W10 (500 l/h):	3,15 kW
Refrigerant / GWP:	Water, light oils or similar
Temperature range:	+1°C - +72°C
Air volume flow:	500 m³/h @ 50 Hz 530 m³/h @ 50 Hz
Mounting:	Internal / External
Dimension HxWxD:	936 x 262 x 146.5 mm
Weight:	18 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Starting current:	1.2 A / 1.3 A
Max. current:	0.7 A / 0.9 A
Max. power:	200 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 10mm
Fuse:	5 A (T)
Connection:	Connection terminals


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview product group Air / Water Heat Exchangers](#)


Performance Graph:

ΔT = Temperature difference between air intake and cooling
P = Cooling capacity



[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut out dimensions:



[click image to enlarge](#)