

Thermoelectric cooling unit TG 3050-24V



Product Features

Brand Name:	SoliTherm Peltier
Order Number:	3050303
Housing Material:	Stainless steel AISI 304 (V2A)
IP class EN 60529:	IP 66 NEMA 4X
Approvals:	CE, cURus, RoHS
Accessories:	?Temperature controller (heating / cooling) 
	Electronic thermostat (cooling) 
	Condensate Kit 
Taric Code:	84158300

Technical data TG 3050-24V

Cooling capacity L35L35:	50 W
Temperature range:	-20°C - +65°C
Air volume flow:	Ambient air circuit: 64 m³/h Cabinet air circuit: 23 m³/h
Mounting:	Recessed
Dimension HxWxD:	206 x 154 x 135 (75) mm
Weight:	3.3 kg
Cut out dimensions:	170 x 120 mm
Voltage / Frequency:	24 V DC
Current L35L35:	2.4 A
Starting current:	3.7 A
Max. current:	2.5 A
Nominal power L35L35:	57.6 W
Max. power:	60 W
Fuse:	4 A (T)
Connection:	Connection terminal block


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview product group Cabinet cooling units - Peltier](#)


Performance Graph:

T = Ambient temperature
 P = Cooling capacity




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut out dimensions:



[click image to enlarge](#)