

Thermoelectric cooling unit TG 3200-48V



Product Features

Brand Name:	SoliTherm Peltier
Order Number:	3200308
Housing Material:	Stainless steel AISI 304 (V2A)
IP class EN 60529:	IP 66 NEMA 4X
Approvals:	CE, cURus, RoHS
Accessories:	Condensate Kit
Taric Code:	84158300

Technical data TG 3200-48V

Cooling capacity L35L35:	250 W
Temperature range:	-20°C - +65°C
Air volume flow:	Ambient air circuit: 120 m³/h Cabinet air circuit: 120 m³/h
Mounting:	Recessed
Dimension HxWxD:	400 x 180 x 171 mm
Weight:	10 kg
Cut out dimensions:	370 x 155 mm
Voltage / Frequency:	48 V DC
Current L35L35:	6 A
Starting current:	14 A
Max. current:	9.3 A
Nominal power L35L35:	400 W
Max. power:	440 W
Fuse:	13 A (T)
Connection:	Connection terminal block


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview product group Cabinet cooling units - Peltier](#)


Performance Graph:

T = Ambient temperature
P = Cooling capacity




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut out dimensions:



[click image to enlarge](#)